

Filename: LTO-75-27x60-30-RJ45-80-NL_rep

Manufacturer: Aquarii

Luminaire: Stage Light

Luminaire Cat: Model: Lieto - 27x60 Degree Beamspread - 75 Watts
- 3000K White Light

Lamp: LED

Lamp Output: 1 lamp, total luminaire Lumens: 6737.3

Max Candela: 34,201.3 at Horizontal: 247.5°, Vertical: 2.5°

Input Wattage: 73.6

Luminous Opening: Circular (Dia: 9.48")


Test Lab: Intertek

Photometry : Type C

CIE Class: Direct

Cutoff Class: Full Cutoff



Nema Type: 4 X 2

**Zonal Lumen Summary**

Zone	Lumens	% Luminaire
0-30	6,138.0	91.1%
0-40	6,538.3	97%
0-60	6,735.8	100%
60-90	1.5	0%
70-100	0	0%
90-120	0	0%
0-90	6,737.3	100%
90-180	0	0%
0-180	6,737.3	100%

Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	2,085.5	31.0%	90-100	0	0%
10-20	2,665.4	39.6%	100-110	0	0%
20-30	1,387.1	20.6%	110-120	0	0%
30-40	400.2	5.9%	120-130	0	0%
40-50	149.8	2.2%	130-140	0	0%
50-60	47.7	0.7%	140-150	0	0%
60-70	1.5	0.0%	150-160	0	0%
70-80	0	0.0%	160-170	0	0%
80-90	0	0.0%	170-180	0	0%



Coefficients Of Utilization - Zonal Cavity Method

		Effective Floor Cavity Reflectance: 20%																			
RCC %:		80				70				50				30				10			
RW %:		70	50	30	0	70	50	30	0	50	30	20	10	50	30	20	10	50	30	20	0
RCR: 0		1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.00	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.02	1.02	1.00
1		1.15	1.13	1.10	1.09	1.12	1.10	1.09	.96	1.06	1.05	1.04	1.03	1.02	1.01	.99	.99	.98	.98	.98	.96
2		1.11	1.07	1.04	1.01	1.09	1.05	1.02	.93	1.02	1.00	.98	.99	.97	.96	.96	.95	.94	.94	.92	.92
3		1.07	1.02	.98	.95	1.05	1.00	.97	.89	.98	.95	.93	.96	.93	.91	.93	.91	.90	.88	.88	.88
4		1.03	.97	.93	.90	1.01	.96	.92	.86	.94	.91	.88	.92	.89	.87	.91	.88	.86	.85	.85	.85
5		1.00	.93	.89	.85	.98	.92	.88	.83	.91	.87	.84	.89	.86	.84	.88	.85	.83	.82	.82	.82
6		.96	.90	.85	.82	.95	.89	.85	.80	.87	.84	.81	.86	.83	.80	.85	.82	.80	.79	.79	.79
7		.93	.86	.82	.79	.92	.86	.81	.77	.84	.81	.78	.83	.80	.78	.82	.79	.77	.76	.76	.76
8		.90	.83	.79	.76	.89	.83	.78	.74	.82	.78	.75	.81	.77	.75	.80	.77	.75	.74	.74	.74
9		.88	.80	.76	.73	.87	.80	.76	.72	.79	.75	.73	.78	.75	.72	.78	.75	.72	.71	.71	.71
10		.85	.78	.73	.71	.84	.77	.73	.70	.77	.73	.70	.76	.73	.70	.75	.72	.70	.69	.69	.69

Luminaire Report Summary

IESNA:LM-63-2002

[LUMCAT] Model: Lieto - 27x60 Degree Beamsread - 75 Watts - 3000K White Light

[LUMINAIRE] Stage Light

[LAMP] LED

[USER DEFINED] 120.04 AC, 621.75 mA, 73.625 W, 0.9864 PF

[TEST]

[TESTLAB] Intertek

[ISSUEDATE] 03/04/2019

[MANUFAC] Aquarii

FILE: CREATED USING ABSOLUTE PHOTOMETRY

FILE: CANDELA MULTIPLIER: 1

FILE: VERTICAL ANGLES: 73, HORIZONTAL ANGLES: 17

FILE: COORDINATE SYSTEM: TYPE C

FILE: UNIT OF MEASURE: STANDARD

FILE: BALLAST FACTOR: 1

Photometrics Pro 1.3.28 copyright 2003-2019 by jSolutions, Inc.

Reported data calculated from manufacturer's data file, based on IES recommended methods.