

**Filename: LTO-75-70-30-RJ45-80-CR\_rep**

Manufacturer: Aquarii

Luminaire: Stage Light

Luminaire Cat: Model: Lieto - 70 Degree Beamspread - 75 Watts -  
3000K White Light - Concentric Rings

Lamp: LED

Lamp Output: 1 lamp, total luminaire Lumens: 5999.5

Max Candela: 7,652.6 at Horizontal: 0°, Vertical: 0°

Input Wattage: 72.7

Luminous Opening: Circular (Dia: 11.04")


Test Lab: Intertek

Photometry : Type C

CIE Class: Direct

Cutoff Class: Full Cutoff


Nema Type: 5 X 5


**Zonal Lumen Summary**

Zone	Lumens	% Luminaire
0-30	3,707.4	61.8%
0-40	5,193.6	86.6%
0-60	5,968.7	99.5%
60-90	30.7	0.5%
70-100	0	0%
90-120	0	0%
0-90	5,999.5	100%
90-180	0	0%
0-180	5,999.5	100%

**Lumens Per Zone**

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	607.3	10.1%	90-100	0	0%
10-20	1,363.4	22.7%	100-110	0	0%
20-30	1,736.7	28.9%	110-120	0	0%
30-40	1,486.2	24.8%	120-130	0	0%
40-50	606.0	10.1%	130-140	0	0%
50-60	169.2	2.8%	140-150	0	0%
60-70	30.7	0.5%	150-160	0	0%
70-80	0	0.0%	160-170	0	0%
80-90	0	0.0%	170-180	0	0%





#### Coefficients Of Utilization - Zonal Cavity Method

		Effective Floor Cavity Reflectance: 20%															
RCC %:		80				70				50				30			
RW %:		70	50	30	0	70	50	30	0	50	30	20	0	50	30	20	0
RCR:		0	1	2	3	4	5	6	7	8	9	10	0	1	2	3	4
		1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.00	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02
		1.13	1.10	1.08	1.05	1.11	1.08	1.06	.93	1.04	1.02	1.00	1.00	.99	.97	.97	.96
		1.07	1.02	.98	.94	1.05	1.00	.96	.86	.97	.94	.91	.94	.91	.89	.91	.89
		1.01	.94	.89	.85	.99	.93	.88	.80	.90	.86	.83	.88	.85	.82	.86	.83
		.96	.88	.82	.77	.94	.87	.81	.74	.84	.80	.76	.82	.78	.75	.80	.77
		.90	.82	.75	.71	.89	.81	.75	.68	.79	.74	.70	.77	.73	.69	.75	.72
		.85	.76	.70	.65	.84	.75	.69	.63	.74	.68	.64	.72	.68	.64	.71	.67
		.81	.71	.65	.60	.80	.70	.64	.59	.69	.64	.60	.68	.63	.59	.67	.62
		.77	.67	.60	.56	.75	.66	.60	.55	.65	.59	.56	.64	.59	.55	.63	.58
		.73	.63	.56	.52	.72	.62	.56	.51	.61	.56	.52	.60	.55	.52	.59	.55
		.69	.59	.53	.49	.68	.58	.53	.48	.58	.52	.48	.57	.52	.48	.56	.51

#### Luminaire Report Summary

IESNA:LM-63-2002

[TEST]

[TESTLAB] Intertek

[ISSUEDATE] 10/17/2019

[MANUFAC] Aquarii

[LUMCAT] Model: Lieto - 70 Degree Beamspread - 75 Watts - 3000K White Light - Concentric Rings

[LUMINAIRE] Stage Light

[LAMP] LED

[\_TOTALLUMINAIRELUMENS] 6121.9

[USER DEFINED] 120.01 AC, 605.7 MA, 72.7 W, 0.9891 PF

FILE: CREATED USING ABSOLUTE PHOTOMETRY

FILE: CANDELA MULTIPLIER: 1

FILE: VERTICAL ANGLES: 73, HORIZONTAL ANGLES: 9

FILE: COORDINATE SYSTEM: TYPE C

FILE: UNIT OF MEASURE: STANDARD  
FILE: BALLAST FACTOR: 1

Photometrics Pro 1.3.28 copyright 2003-2019 by jSolutions, Inc.  
Reported data calculated from manufacturer's data file, based on IES recommended methods.